

BECKER et al.

Appl. No.: 09/424,660

rotating the first substrate with a rotary drive;  
positioning the second substrate onto the layer of viscous fluid formed on the first substrate with a connecting means;  
spinning off excess viscous fluid of the layer between the first substrate and the second substrate with a rotary centrifugal drive; and  
controlling a thickness of the layer formed on the first substrate to a predetermined thickness by controlling at least one of the dosing pump, a position of the dosing arm with respect to the first substrate, a rotary speed of the rotary drive, and a rotary speed of the rotary centrifugal drive in response to at least one of a temperature of the first substrate, a temperature of the second substrate, a temperature of the viscous fluid, and a viscosity of the viscous fluid.

24. (Twice Amended) An apparatus for bonding a first planar substrate to a second planar substrate by a bonding material in the form of a viscous fluid, comprising:  
a pump that pumps the viscous fluid;  
a dosing arm, connected to the pump and positioned over the first substrate, that doses the first substrate with the viscous fluid and forms a layer of the viscous fluid on the first substrate;  
a plate that supports the first substrate;  
a rotary drive that rotates the plate;  
a connecting means that positions the second substrate onto the layer of viscous fluid formed on the first substrate;  
a rotary centrifugal drive that spins off excess viscous fluid of the layer between the first substrate and the second substrate; and  
a controller that controls a thickness of the layer to a predetermined thickness by controlling at least one of the dosing pump, a position of the dosing arm, a rotary speed of

BECKER et al.

Appl. No.: 09/424,660

Sub 7  
G2  
G3  
G4  
G5  
G6  
G7  
G8  
G9  
G10  
G11  
G12  
G13  
G14  
G15  
G16  
G17  
G18  
G19  
G20  
G21  
G22  
G23  
G24  
G25  
G26  
G27  
G28  
G29  
G30  
G31  
G32  
G33  
G34  
G35  
G36  
G37  
G38  
G39  
G40  
G41  
G42  
G43  
G44  
G45  
G46  
G47  
G48  
G49  
G50  
G51  
G52  
G53  
G54  
G55  
G56  
G57  
G58  
G59  
G60  
G61  
G62  
G63  
G64  
G65  
G66  
G67  
G68  
G69  
G70  
G71  
G72  
G73  
G74  
G75  
G76  
G77  
G78  
G79  
G80  
G81  
G82  
G83  
G84  
G85  
G86  
G87  
G88  
G89  
G90  
G91  
G92  
G93  
G94  
G95  
G96  
G97  
G98  
G99  
G100

the rotary drive, and a rotary speed of the rotary centrifugal drive in response to at least one of a temperature of the first substrate, a temperature of the second substrate a temperature of the viscous fluid, and a viscosity of the viscous fluid.

25. (Twice Amended) The apparatus according to claim 24, further comprising:  
at least one sensor that measures the thickness of the layer, wherein the controller controls at least one of the dosing pump, the position of the dosing arm, the rotary speed of the rotary drive, and the rotary speed of the rotary centrifugal drive to automatically adjust deviations between the measured thickness of the layer and the predetermined thickness to within at least one tolerance.

27. (Twice Amended) The apparatus according to claim 24, wherein the controller controls the thickness of the layer of viscous fluid by controlling at least one of a connecting pressure of the connecting means and a rotary speed of the rotary centrifugal drive.

28. (Amended) The method according to claim 14, further comprising:  
controlling the thickness of the layer of viscous fluid by controlling at least one of a connecting pressure of the connecting means and a rotary speed of the rotary centrifugal drive.

See the attached Appendix for the changes made to effect the above claims.

Please add claim 29 as follows:

29. (New) The apparatus according to claim 25, wherein the at least one tolerance includes a range in at least one of a radial direction of the first substrate and a tangential direction of the first substrate.